

# Cold Pressure Washers

INDUSTRIAL USAGE



OLD VALUES. NEW IDEAS.



Alkota's heavy-duty cold pressure washers are powerful and portable for the toughest cleaning situations.



**MODEL 430S**  
ELECTRIC



**MODEL 425S**  
GAS

## INDUSTRIAL USE PRESSURE WASHERS

- Perfect for blasting away dirt and mud
- Available in electric or gas engines
- Ball bearing pneumatic wheels for portability
- Heavy-duty construction for dependability and durability
- Ideal for hog producers, farms, factories, construction equipment, paint contractors and other general use

## DELUXE COLD PRESSURE WASHER SPECIFICATIONS

MODEL	425S	435S	535S	445S	545S	555S	835S
CAPACITY	4 GPM	4 GPM	5 GPM	4 GPM	5 GPM	5 GPM	8 GPM
PRESSURE	2500 PSI	3000 PSI	3000 PSI	4000 PSI	4000 PSI	5000 PSI	3000 PSI
ENGINE/MOTOR	9 HP, Vanguard, Oil Alert, Overhead Valve	11 HP, Vanguard, Oil Alert, Overhead Valve	16 HP, Vanguard, Oil Alert, Overhead Valve	16 HP, Vanguard, Oil Alert, Overhead Valve	18 HP, Vanguard, Oil Alert, Overhead Valve	25 HP, Kohler, Oil Alert, Overhead Valve	25 HP, Kohler, Oil Alert, Overhead Valve
PUMP	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers
HOSE	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'
WAND	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger
DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt
GAS TANK	2.08 Gallons	2.08 Gallons	4.7 Gallons	4.7 Gallons	4.7 Gallons	5.75 Gallons	5.75 Gallons
WHEELS	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic	13" Ball Bearing Pneumatic
DIMENSIONS	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-29 1/4"	L-49" H-35" W-31 1/2"	L-49" H-35" W-31 1/2"
SHIPPING WEIGHT	325 lbs.	345 lbs.	385 lbs.	375 lbs.	385 lbs.	435 lbs.	435 lbs.

## ELECTRIC COLD PRESSURE WASHER SPECIFICATIONS

MODEL	420S	430S	520S	530S	540S	550S	830S
CAPACITY	3.7 GPM	3.8 GPM	4.8 GPM	5 GPM	5 GPM	5 GPM	8 GPM
PRESSURE	2000 PSI	3000 PSI	2000 PSI	3000 PSI	4000 PSI	5000 PSI	3000 PSI
ENGINE/MOTOR	5 HP, 230 V, 1 PH	8 HP, 230 V, 1 PH	6 HP, 230 V, 1 PH	10 HP, 230 V, 1 PH	15 HP, 230 V, 3 PH	20 HP, 230 V, 3 PH	20 HP, 230 V, 3 PH
PUMP	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers	Triplex, Oil Bath Ceramic Plungers
HOSE	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'	3/4" x 50'
WAND	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger	Trigger
DRIVE	Belt	Belt	Belt	Belt	Belt	Belt	Belt
DIMENSIONS	L-48 1/2" W-29" H-32 1/2"	L-48 1/2" W-29" H-32 1/2"	L-48 1/2" W-29" H-32 1/2"	L-53" W-33" H-32 1/2"	L-53" W-33" H-32 1/2"	L-53" W-33" H-32 1/2"	L-53" W-33" H-32 1/2"



OLD VALUES. NEW IDEAS.

Alcester, South Dakota 57001  
1.800.255.6823 [www.alkata.com](http://www.alkata.com)

