

Four Wheel Series



OLD VALUES. NEW IDEAS.



Easy mobility
with the powerful
new four wheel
oil fired series.





MODEL SHOWN: THE TINY TERROR XTREME SERIES

MOBILITY

Alkota's Hot High Pressure Washers are now even more mobile with the new Four Wheel Series. The X4 Cleaning Crew and the AX4 Tiny Terror can be moved with ease, so you can bring the washer to the job instead of bringing the job to the washer.

OIL FIRED

- Engineered with oil bath type pumps designed for rugged usage
- Easy access controls
- Precise chemical metering, stainless steel float tanks and rotary on/off switches
- Pressure atomizing burner coupled with a cold water wrap provides a highly efficient heating system
- Perfect for farms, service stations, repair shops, or rental fleets
- Hose reel optional



MODEL SHOWN: X4 CLEANING CREW SERIES



TAKE YOUR PICK

- More than a dozen four wheel high pressure washers make it easy to find just the right one for you
- Choose from six different capacities, ranging from 1.5 GPM to 4.8 GPM
- Automatic ignition standard
- Motors range from 2.3 HP to 10 HP
- All models available in Xtreme series with stainless steel

MODEL SHOWN: X4 CLEANING CREW XTREME SERIES



MODEL SHOWN: X4 CLEANING CREW SERIES

FEATURES

- 4 tubed pneumatic wheels
- Adjustable front axle for proper weight distribution
- Adjustable height push handle
- Industrial strength 1 1/2" tube frame
- Powder-coated paint finish for durability
- Belt drive pump standard
- 50' hose, shut off gun and 36" insulated wand
- Hose reel optional



OLD VALUES. NEW IDEAS.

SPECIFICATIONS

OIL FIRED HIGH PRESSURE WASHERS

MODEL	213AX4	120AX4	216AX4	311AX4	320AX4	216X4	311X4	320X4	324X4	330X4	418X4	420X4
Capacity*	2.0 GPM	1.5 GPM	2.0 GPM	3.0 GPM	3.0 GPM	2.0 GPM	3.0 GPM	3.0 GPM	3.0 GPM	3.0 GPM	4.0 GPM	3.7 GPM
Pressure*	1300 PSI	2000 PSI	1600 PSI	1100 PSI	2000 PSI	1600 PSI	1100 PSI	2000 PSI	2400 PSI	3000 PSI	1800 PSI	2000 PSI
Pump	Triplex, Oil Bath, Direct Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive
Motor/Voltage**	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	4 HP, 230 V, 1 PH, Fuse for 20 Amp.	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	2.3 HP, 115 V, 1 PH, Fuse for 20 Amp.	4 HP, 230 V, 1 PH, Fuse for 20 Amp.	5 HP, 230 V, 1 PH, Fuse for 30 Amp.	6 HP, 230 V, 1 PH, Fuse for 30 Amp.	5 HP, 230 V, 1 PH, Fuse for 30 Amp.	5 HP, 230 V, 1 PH, Fuse for 30 Amp.
Coil (Steel Pipe) Cold water wrap, spiral heating section	95', Schedule 40	95', Schedule 40	95', Schedule 40	95', Schedule 40	95', Schedule 40	126', Schedule 40	126', Schedule 40	126', Schedule 40	126', Schedule 80	126', Schedule 80	158', Schedule 40	126', Schedule 40
Burner, Pressure atomizing, auto ignition, fuel consumption	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH	Kero, or #1 Diesel, 133,000 BTU, .95 GPH	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH	Kero, or #1 Diesel, 175,000 BTU, 1.25 GPH	Kero, or #1 Diesel, 273,000 BTU, 1.95 GPH	Kero, or #1 Diesel, 273,000 BTU, 1.95 GPH	Kero, or #1 Diesel, 273,000 BTU, 1.95 GPH	Kero, or #1 Diesel, 273,000 BTU, 1.95 GPH	Kero, or #1 Diesel, 385,000 BTU, 2.75 GPH	Kero, or #1 Diesel, 350,000 BTU, 2.50 GPH
Fuel Tank	Plastic, 4.5 Gal.	Plastic, 4.5 Gal.	Plastic, 4.5 Gal.	Plastic, 4.5 Gal.	Plastic, 4.5 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.
Stack Size	8"	8"	8"	8"	8"	8"	8"	8"	8"	8"	8"	8"
Temp. Control	Standard	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Chemical	Low Pressure Injector	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
Float Tank	N/A	Plastic	Plastic	Plastic	Plastic	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Steam Capacity (Optional)	N/A	N/A	N/A	N/A	N/A	60 GPH	90 GPH	90 GPH	90 GPH	90 GPH	120 GPH	120 GPH
Dimensions	L - 40" W - 27" H - 40"	L - 40" W - 27" H - 40"	L - 40" W - 27" H - 40"	L - 40" W - 27" H - 40"	L - 40" W - 27" H - 40"	L - 46" W - 31" H - 49"	L - 46" W - 31" H - 49"	L - 46" W - 31" H - 49"	L - 46" W - 31" H - 49"	L - 46" W - 31" H - 49"	L - 54" W - 32" H - 49"	L - 46" W - 31" H - 49"
Shipping Weight	400 lb.	420 lb.	420 lb.	420 lb.	420 lb.	535 lb.	535 lb.	535 lb.	535 lb.	545 lb.	400 lb.	545 lb.

MODEL	423X4	425X4	430XM4	430XM	435X4	518X4	523X4	530X4 3 Phase	530X4 1 Phase
Capacity*	3.7 GPM	3.5 GPM	3.8 GPM	3.8 GPM	3.8 GPM	4.8 GPM	4.8 GPM	4.8 GPM	4.8 GPM
Pressure*	2300 PSI	2500 PSI	3000 PSI	3000 PSI	3500 PSI	1800 PSI	2300 PSI	3000 PSI	3000 PSI
Pump	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive	Triplex, Oil Bath, Belt Drive
Motor/Voltage**	6 HP, 230 V, 1 PH, Fuse for 30 Amp.	6 HP, 230 V, 1 PH, Fuse for 30 Amp.	8 HP, 230 V, 1 PH, Fuse for 40 Amp.	8 HP, 230 V, 1 PH, Fuse for 40 Amp.	10 HP, 230 V, 3 PH, Fuse for 30 Amp.	6 HP, 230 V, 1 PH, Fuse for 30 Amp.	8 HP, 230 V, 1 PH, Fuse for 30 Amp.	10 HP, 230 V, 3 PH, Fuse for 30 Amp.	10 HP, 230 V, 1 PH, Fuse for 50 Amp.
Coil (Steel Pipe) Cold water wrap, spiral heating section	158', Schedule 80	126', Schedule 80	158', Schedule 80	126', Schedule 80	126', Schedule 80	158', Schedule 40	158', Schedule 80	158', Schedule 80	158', Schedule 80
Burner, Pressure atomizing, auto ignition, fuel consumption	Kero, or #1 Diesel, 385,000 BTU, 2.75 GPH	Kero, or #1 Diesel, 350,000 BTU, 2.5 GPH	Kero, or #1 Diesel, 385,000 BTU, 2.75 GPH	Kero, or #1 Diesel, 350,000 BTU, 2.5 GPH	Kero, or #1 Diesel, 350,000 BTU, 2.5 GPH	Kero, or #1 Diesel, 540,000 BTU, 3.85 GPH	Kero, or #1 Diesel, 540,000 BTU, 3.85 GPH	Kero, or #1 Diesel, 540,000 BTU, 3.85 GPH	Kero, or #1 Diesel, 540,000 BTU, 3.85 GPH
Fuel Tank	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.	Plastic, 8 Gal.
Stack Size	8"	8"	8"	8"	8"	8"	8"	8"	8"
Temp. Control	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Chemical	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered	Precise Metered
Float Tank	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel
Steam Capacity (Optional)	120 GPH	120 GPH	120 GPH	120 GPH	120 GPH	150 GPH	150 GPH	150 GPH	150 GPH
Dimensions	L - 54" W - 32" H - 49"	L - 46" W - 32" H - 49"	L - 54" W - 32" H - 49"	L - 46" W - 32" H - 49"	L - 46" W - 32" H - 49"	L - 46" W - 32" H - 49"	L - 54" W - 32" H - 49"	L - 54" W - 32" H - 49"	L - 54" W - 32" H - 49"
Shipping Weight	715 lb.	575 lb.	715 lb.	585 lb.	575 lb.	665 lb.	725 lb.	730 lb.	730 lb.

Note: All 115 volt units have ground fault interrupters standard.

*Gallons and pressure may vary \pm 5% due to manufacturing tolerances in components.

**Special voltages on request. Gallonages and pressure may be less on 3 phase current.

Xtreme models same specifications plus Schedule 80 coils, Hi-Limit Control, Fuel Solenoid and Stainless Steel Coil Wrappers (X4X models).

ENGLISH TO METRIC CONVERSION CHART

- 1 gallon/minute = 3.78 liters/minute
- 1 horsepower = .746 watts
- 100 PSI = 7.03 Kg/cm²
- 1 foot = .3048 meters
- 1 inch = 2.54 centimeters
- 1 pound = .45359 kilograms



OLD VALUES. NEW IDEAS.

Alcester, South Dakota 57001
1.800.255.6823 www.alkota.com

